



NVIDIA JETSON AGX XAVIER MODULE

A NEW AI MILESTONE FOR AUTONOMOUS MACHINES

Server-class performance in the palm of your hand.

The NVIDIA® Jetson AGX Xavier™ module delivers up to 32 TOPS of accelerated computing capability in a compact form factor consuming under 30 Watts. This gives you more than 20X the performance and 10X the energy efficiency of its predecessor, the NVIDIA Jetson™ TX2.

This advanced system-on-module is powered by the NVIDIA Xavier SoC and designed specifically for autonomous machines. Heterogeneous accelerated computing architecture delivers advanced edge capabilities. Plus, it comes with integrated memory, storage, power management, and an innovative thermal design to enable faster time to market. Run modern AI workloads and solve problems in areas like manufacturing, logistics, retail, service, agriculture, smart cities, and healthcare.

Jetson AGX Xavier is supported by NVIDIA JetPack, which includes a board support package (BSP), an Ubuntu Linux OS, NVIDIA CUDA®, cuDNN, and TensorRT™ software libraries for deep learning, computer vision, GPU computing, multimedia processing, and much more. It's also supported by the NVIDIA DeepStream SDK, which delivers a complete toolkit for real-time situational awareness through intelligent video analytics (IVA). This helps you boost performance and accelerate software development, while reducing development cost and effort.

Learn more at www.developer.nvidia.com/jetson-agx-xavier.

KEY FEATURES

Module

- > 512-Core NVIDIA Volta™ GPU with Tensor Cores
- > (2x) NVDLA Engines
- > 8-Core ARM® v8.2 64-Bit Carmel CPU
- > 16 GB 256-Bit LPDDR4x
- > 32 GB eMMC 5.1 Flash Storage
- > 7-Way VLIW Vision Accelerator Processor

Power

- > Voltage Input 5 V, 9 V-20 V
- > Module Power: 10 W-30 W

Environment

- > Operating Temperature: -25°C to 80°C measured on the TTP surface
- > Storage Temperature: -25°C to 80°C
- > Humidity: 95% RH, -10°C to 65°C (non-operational)
- > Vibration: 5 G RMS 10 to 500 Hz (random/ sinusoidal)
- > Shock: 50 G, half sine 11 ms duration

NVIDIA JETSON AGX XAVIER

TECHNICAL SPECIFICATIONS

| | |
|--------------------|---|
| GPU | 512-Core Volta GPU with Tensor Cores |
| DL Accelerator | {2x} NVDLA Engines |
| CPU | 8-Core ARM v8.2 64-Bit CPU, 8 MB L2 + 4 MB L3 |
| Memory | 16 GB 256-Bit LPDDR4x 137 GB/s |
| Display | HDMI 2.0, eDP1.4, DP HBR3 |
| Storage | 32 GB eMMC 5.1 |
| Vision Accelerator | 7-Way VLIW Vision Processor |
| Encoder/Decoder | {2x} 4Kp60 HEVC/{2x} 8Kp30 12-Bit Support |
| CSI | {16x} CSI-2 Lanes |
| PCIE/SLVS/USB/UFS | {8x} PCIe Gen4 / {8x} SLVS-EC {3x} USB 3.1 Single Lane UFS |
| Other | UART, SPI, CAN, I²C, I²S, DMIC, GPIOs |
| Connectivity | Gigabit Ethernet |
| Power | 10 W~30 W |
| Size | 87 mm x 100 mm |
| Mechanical | 699 pin Molex Mirror Mex Connector Integrated Thermal Transfer Plate |

To learn more about NVIDIA Jetson AGX Xavier, visit www.pny.eu

© 2021 NVIDIA Corporation. All rights reserved. NVIDIA, the NVIDIA logo, Jetson, Xavier, AGX Xavier, CUDA and NVIDIA Volta are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated. ARM, AMBA and ARM Powered are registered trademarks of ARM Limited. Cortex, MPCore and Mali are trademarks of ARM Limited. All other brands or product names are the property of their respective holders. "ARM" is used to represent ARM Holdings plc; its operating company ARM Limited; and the regional subsidiaries ARM Inc.; ARM KK; ARM Korea Limited.; ARM Taiwan Limited; ARM France SAS; ARM Consulting (Shanghai) Co. Ltd.; ARM Germany GmbH; ARM Embedded Technologies Pvt. Ltd.; ARM Norway, AS and ARM Sweden AB. Features, pricing, availability, and specifications are all subject to change without notice. JUL21



PNY Technologies Europe
9 rue Joseph Cugnot, 33708 Mérignac cedex | France
T +33 (0) 5 56 13 75 75 | pnypro@pny.eu
For more information visit: www.pny.eu